

## F0903 | GUARD BAR INTERLOCK



### FEATURES & BENEFITS

- \* Robust design.
- \* Anodised aluminium body.
- \* Viton seals throughout with low friction treatment on bearing surfaces.
- \* Stainless steel locking pin.
- \* Vehicle's brakes automatically applied when loading and discharging.
- \* Access prevented to all discharge valves.
- \* Bolt holes for fitting.
- \* Weight: 1.00 kg.

The F0903 Guard Bar Interlocks are designed to pneumatically lock the guard bar, which prevents access to the system's discharge valves, except when loading or unloading. They can also prevent movement of the vehicle by interlocking to the brakes during loading and discharge.

#### WHEN SPECIFYING DIP INTERLOCK ASSEMBLIES FOR YOUR VEHICLE, THE FOLLOWING POINTS SHOULD BE CONSIDERED:

- \* One unit is required per Guard Bar.
- \* The Guard Bar should not rest on the interlock. Separate provision should be made for this – refer to the installation sheet for details.

# F0903

*Better by Design*



**EMCO WHEATON**

*A Gardner Denver Product*

EMCO WHEATON UK Limited  
 Channel Road · Westwood Industrial Estate  
 Margate, Kent CT9 4JR · UK  
 Phone + 44 1843 221521 · Fax +44 1843 295444  
[www.emcowheaton.com](http://www.emcowheaton.com) · [assist@emcowheaton.com](mailto:assist@emcowheaton.com)